


SS-15DPXG-CSUTL-M3(SM) | 3.0 MP 4G Camera. Compatible with 5G Sim Card



Key Features

- Progressive Scan CMOS Sensor.
- Mobile Phone Monitoring (iOS, Android).
- Human & Sound Detection.
- Ingress Protection IP67.
- Video Encoding H.265X.



Parameter	Details
Model	SS-15DPXG-CSUTL-M3(SM)
Make	SECURUS
Image Sensor	1/2.9" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0MP)
Minimum Illumination	Color: 0.005Lux@F1.2; B/W: 0.001Lux@F1.2
Day/Night	Auto (ICR) / Color / Black & White
DWDR	Auto
BLC (Back Light Compensation)	On/Off
Night Vision	1Pcs Warm Light LED
Night Light Temperature	3000~3300K
Night Vision Technology	Colorsense [®] Technology
Night Vision Distance	20 Meters
Lens Mount	2.8mm/3.6mm/4.0mm
Lens Type	Board Lens
Network Type	4G (Compatible with 5G Sim Card)
4G Standard	LTE-TDD/LTE-FDD/TD-SCDMA/ WCDMA
4G Frequency Band	LTE-FDD : B1/B3/B5/B8, LTE-TDD : B34/B38/B39/B40/B41; WCDMA:B1/B5/B8

Parameter	Details
Network Interface	10/100 MBPS RJ45 Connector
Network Protocol	HTTP, TCP, ARP, RTMP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
ONVIF Protocol	Supported (Ethernet Port Only)
SD Card	Supported (Max: 512 GB)
Video Bitrate	128kbps ~ 8Mbps
Video Compression	H.265X, H.264
Video Streams	HD/SD, Rate Adaptation, Triple Stream
Image Resolution	Mainstream: 2304*1296, 1920*1080; Auxiliary stream: 1280*720, 704*576, 640*480, 352*288 Snapstream: 704*576, 640*480, 352*288
Frame Rate	1296P @ 15FPS; 1080P @ 15FPS; 720P @ 15FPS; D1 @ 15FPS
DNR	2DNR, 3DNR (Digital Noise Reduction)
Shutter Speed	1/25s ~ 1/100000s (Shutter Adaptation)
Digital Zoom	Supported (Max: 16X)
Audio Input	Yes; (Built-in Mic)
Audio Output	Yes; (Built-in Speaker)
Audio Compression	G.711A

Parameter	Details
Intelligent AI Feature	Human Detection, Sound Detection
Alarm Notification	Push Notification on Mobile Application
Image reversal	Vertical Flip / Horizontal Mirror
Privacy Mask	Up to 4 Areas
Antenna	Single Antenna
Antenna Frequency Range	824-960MHz, 1710-2690MHz
Antenna Impedance	50Ω
Antenna VSWR	≤3.0
Antenna Gain	3dBi
Antenna Bandwidth	136/980MHz
Housing Material	ABS Plastic
Weight	≤0.5 KGs
Dimension	97W X 110L X 1110H (mm)
Operation Temperature	-10°C ~ +65°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V
Power Consumption	≤5W
Ingress Protection	IP67

Parameter	Details
Mobile Application	PVMS Pro 4K
Mobile OS	Android, iOS
Browsers Supported	Chrome, Edge, Opera, Mozilla Firefox
Certifications	CE, FCC, RoHS

Securus Overview

Securus CCTV is one of the Largest Indian Manufacturer & Supplier of Video Surveillance Products like High Definition Cameras, Standalone Recorders, Network Recorders, POE Switches, Video Management Surveillance Software, CCTV & Networking Cables for Surveillance & Other Surveillance Products & Solutions. Powered by In House R&D Team & State-of-the Art Factory in Electronic Zone Gandhinagar. We Manufacture Products under the **Make in India** Initiative.



Securus AI Technology



Head Office

K.M. ELECTRONIC CABLES PRIVATE LIMITED
"K.M. House", Near C.U. Shah College,
Ahmedabad, Gujarat-380014

Factory

K.M. ELECTRONIC CABLES PRIVATE LIMITED
B-20, GIDC Electronics Estate, Sector 25,
Gandhinagar, Gujarat-382024

Email

sales@securusctv.com

Securus Helpline

85911 85511

Securus Website

www.securusctv.com