

SS-N08GP-S2 | 8 Ports 10/100/1000 POE + 2 SFP Ports



Key Features

- 8 x 1000 Mbps Gigabit Ports
2 SFP Ports
- Supports VLAN/CCTV Mode to POE up-to 250 Meters
- Can supply Max 30W Power on Each Port
- Max Power Budget of 120W
- Compliance with IEEE802.3 af/at Standards
- Supports IEEE802.3x Full-Duplex Flow Control
- Supports Auto MDI/MDIX
- Excellent Lightning Protection up-to 6KV
- Easy to Install and Operate

| Parameter | Details |
|-------------------------|--|
| Model | SS-N08GP-S2 |
| Make | SECURUS |
| Network Ports | 8 Gigabit Ports : 10/100/1000 Mbps 2 SFP Ports |
| Transmission Distance | 8 Gigabit Ports : 100 Mtrs @ 1000 Mbps; 250 Mtrs @ 10 Mbps |
| Transmission Media | Cat5e/Cat6 Standard UTP Cable |
| POE Standard | IEEE802.3 af/at Standard |
| POE Power Supply Method | End-Span Method |
| POE Power Supply Watt | Each Port ≤30W, Total Power 120W |
| Network Standard | IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3az, IEEE802.3z |
| Swap Mode | Store & Forward |
| Data Caching Mechanism | 1 M |
| MAC Address List | 2 K |
| Reset Button | Available |
| VLAN Switch | Available |

| Parameter | Details |
|-----------------------------------|------------------------------|
| Communication Protocols | IPv4 and IPv6 Compatible |
| Power Supply Mode | Power Adaptor |
| Voltage Range | DC48V ~ 56V |
| Power Consumption | Device: <5W ; Adaptor: <120W |
| Working Temperature | 0°C ~ 55°C |
| Storage Temperature | -40°C ~ 65°C |
| Humidity | 0 ~ 95% |
| Dimensions (L x W x H) | 220mm x 105mm x 28mm |
| Color (Chasis) | Black |
| Weight | 612 Grams |
| Mean Time Between Failures (MTBF) | >50000 Hours |
| Certifications | CE, FCC, RoHS |