


## SS-NC20L2CP-YXF-M8(4K) | 8.0 MP AI Network Bullet Camera



### Key Features

- Progressive Scan CMOS Sensor.
- Aluminum + ABS Housing.
- People Counting Feature.
- Ingress Protection IP67.
- Video Encoding H.265AI/H.265+.



Parameter	Details
Model	SS-NC20L2CP-YXF-M8(4K)
Make	<b>SECURUS</b>
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	3840 x 2160 (8.0 MP), 2880 x 1616 (5.0 MP), 2560 x 1440 (4.0 MP), 2304 x 1296 (3.0MP), 1920 x 1080 (2.0 MP)
Minimum Illumination	0.01Lux @ (F1.2,AGC ON),0Lux with IR
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≥120db
IR LED	18 SMD IR LED
IR Distance	30 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/50s ~ 1/10,000s
Lens Mount	3.6mm / 4.0mm / 6.0mm
Lens Type	Board Lens
Network Interface	1*RJ45 Connector 10/100 MBPS
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP,FTP, DHCP
SD Card	Supported (Max: 512GB) (Optional)

Parameter	Details
Video Encoding	H.265A1/H.265+/H.265/H.264+/H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Main Stream : 3840 x 2160; @15FPS; 2880 x 1616@25FPS; 2560 x 1440; @25FPS; 1920 x 1080; 25 FPS Sub Stream 1: 800 x 448; @25FPS
Digital Zoom	16X
Audio Input	Yes; 1Ch; 2Vp-p 1k $\Omega$ Impedence (Optional)
Audio Output	Yes; 1Ch; 16 $\Omega$ Impedence (Optional)
Audio Compression	G.711, Support bidirectional talk, Audio & Video synchronization
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	N/A
Intelligent AI Feature	Human Detection, Face Detection, People Counting, Customer Flow Statistics
Customer Flow Values	Enter, Leave & Pass Through (Max : 65,500 Per Day)
Statistics Reports	Daily, Weekly, Monthly & Annual Statistics
Graph Reports	Tabular Report, Line Chart & Histogram
Reports Export	Export to Excel Sheet (.xls)
ONVIF	ONVIF Profile S & T Conformant

Parameter	Details
Power Consumption	≤3W
Operation Temperature	-10°C ~ + 65°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V/2A input, PoE (IEEE802.3af)(Class 0)
Mobile Monitoring	RMEye Pro (iOS & Android)
Dimensions	180mm x 70mm x 70mm
Weight	≤1.0 KGs (No HDD)
Ingress Protection	IP67
Certifications	CE, FCC, RoHS