


## SS-NC20L2XP-CSUTL-M3(S) | 3.0 MP IP UTILITY BULLET CAMERA



### Key Features

- Built-in Audio.
- Progressive Scan CMOS Sensor.
- Colorsense<sup>®</sup> Technology.
- Ingress Protection IP67.
- Video Encoding H.265AI/H.265+.



Parameter	Details
Model	SS-NC20L2XP-CSUTL-M3(S)
Make	<b>SECURUS</b>
Product Range	Utility Range
Image Sensor	1/2.7" Progressive Scan CMOS
Image Pixels	2304 x 1296 Pixels (3.0 MP)
Minimum Illumination	Color: 0.005Lux@F1.2; B/W: 0.001Lux@F1.2
Day/Night	Auto (ICR) / Color / Black & White
WDR (Wide Dynamic Range)	≤140db
IR LED	2Pcs IR LED
IR LED Technology	Colorsense® Technology
IR Distance	20 ~ 40 Meters
Shutter Type	Manual/Auto
Shutter Speed	1/25s ~ 1/100000s
Lens Mount	2.8mm/3.6mm/4.0mm/6.0mm
Lens Type	Board Lens
Network Interface	10/100 MBPS RJ45 Connector

Parameter	Details
Network Protocol	HTTP, TCP, ARP, RTSP, RTP, UDP, RTCP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, IPv4/v6, SNMP, QoS, UPnP, NTP
Video Encoding	H.265AI/H.265+/H.265/H.264+/H.264
Video Bitrate	128kbps ~ 8Mbps
Video Streams	Triple Stream
Video Stream Resolution	Max : 2304 x 1296; 1920 x 1080; 720 x 576; 25/30 FPS
Digital Zoom	Supported (Max: 16X)
Audio Input	Yes; 1Ch; 2Vp-p 1k $\Omega$ Impedence
Audio Output	Yes; 1Ch; 16 $\Omega$ Impedence
Audio Compression	G.711
Image Setup	Mirror Image/Reverse/Color Settings
Alarm	N/A
Intelligent AI Feature	Face Detection, Human Detection, Active Deterrence, Line Crossing, Trip Wire
Operation Temperature	-10°C ~ +65°C
Operation Humidity	0% ~ 90%
Power Supply	DC12V, PoE (IEEE802.3af)(Class 0)

Parameter	Details
Power Consumption	≤3.6W without IR; ≤6W with IR
Multiple Browsers	Supports (Chrome, Mozilla, Edge, Opera)
Housing Material	Aluminium + ABS
Dimensions	180mm x 70mm x 70mm
Weight	≤0.5 KGs
Ingress Protection	IP67
Certifications	CE, FCC, RoHS