


## **SS-NE15XSP-M5 | 6.0 MP Outdoor 15X IP Speed Dome Camera**



### **Key Features**

- Progressive Scan CMOS Sensor.
- POE Power Supply.
- Face Detection and Vehicle Detection.
- ONVIF Conformant.
- Video Encoding H.265AI/H.265+.




Parameter	Details
Model	SS-NE15XSP-M5
Make	SECURUS
Image Sensor	1/2.8", 6.0 Megapixel, progressive scan, CMOS
Lens	5mm ~ 75mm (15x optical zoom)
Auto control IR LED	PWM
IR Distance	6Pcs IR LEDs
Iris	Auto/Manual; F1.6 ~ F4.8
Shutter	Auto/Manual.
Shutter Time	1/25s ~ 1/100000s
Minimum Illumination	Color: 0.005Lux@F1.2 B/W: 0.001Lux@F1.2 (IR ON: 0.0 Lux)
S/N Ratio	≥ 50dB
Day/Night Mode	IR-Cut filter with auto switch (ICR)
IR Distance	60 Meters
Audio Compression	G.711
Audio Input	Supports built-in Audio (Optional)
Video Compression	H.265AI, H.265+, H.265, H.264
Video Resolution	3072 x 2048 Pixels (6.0 MP) (Max)
CVBS Output	Supports 1 x BNC Video Output (Optional)
Frame Rate	6MP; 5MP; 3MP; 2MP @20/25/30FPS
Video Streaming	Triple Streams

Parameter	Details
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 Areas
Digital Zoom	Supports
Alarm I/O	1/1 (Optional)
Intelligent AI Feature	Face Detection, Vehicle Detection, Active Deterrence, Line Crossing, Trip Wire, Human Auto Tracking
Network Protocols	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, 802.1X, P2P
Software Control	IE, CMS, P2P(P6SLite)
Pan Range	0°~360°
Pan Speed	0°/s ~ 80°/s
Tilt Range	-0° ~ +93°
Tilt Speed	0°/s ~ 40°/s
Auto Flip	Pan: 180°; Tilt: 93°
Presets	220/500 Presets
Dwell Time	1s ~ 60s Selectable
Guard Tours	3 Tours
Guard Points	Max: 16 Points
Communication Protocol	Pelco-D; Pelco-P
Baud Rate	9600BPS (Default)

Parameter	Details
A-B Scan	User programmable (Scan Speed 1-64 levels setting available)
BLC	Support
AGC	Auto/Manual
WB	Auto/Manual/Indoor/Outdoor
DNR	2DNR,3DNR
WDR	DWDR
Park Time	1 ~ 60 Minutes
SD Card	Supported (Max: 512 GB) (Optional)
Network	10M/100M Base-TX Ethernet
Power Supply	12V 3Amp/POE(802.3at)
Power Consumption	≤25W (Without IR)
Multiple Browsers	Supports (Chrome, Mozilla, Edge, Opera)
Housing Material	Aluminum + ABS
Weight	5.28 KGs
Working Temperature	-40°C ~ +60°C
Working Humidity	≤90% RH (Non Condensing)
Ingress Protection	IP67
Lightning Protection	Transient Voltage 6000V
Certifications	CE, FCC, ROHS

## Securus Overview

Securus CCTV is one of the Largest Indian Manufacturer & Supplier of Video Surveillance Products like High Definition Cameras, Standalone Recorders, Network Recorders, POE Switches, Video Management Surveillance Software, CCTV & Networking Cables for Surveillance & Other Surveillance Products & Solutions. Powered by In House R&D Team & State-of-the Art Factory in Electronic Zone Gandhinagar. We Manufacture Products under the **Make in India** Initiative.



## Securus AI Technology



### Head Office

K.M. ELECTRONIC CABLES PRIVATE LIMITED  
"K.M. House", Near C.U. Shah College,  
Ahmedabad, Gujarat-380014

### Factory

K.M. ELECTRONIC CABLES PRIVATE LIMITED  
B-20, GIDC Electronics Estate, Sector 25,  
Gandhinagar, Gujarat-382024

### Email

[sales@securuscctv.com](mailto:sales@securuscctv.com)

### Securus Helpline

85911 85511

### Securus Website

[www.securuscctv.com](http://www.securuscctv.com)