


SS-N8016RV-H2-M5 | AI Network Video Recorder



Key Features

- Playback and Backup modes.
- ONVIF Support.
- Face Detection.
- RMEye Pro Application.
- Video Compression H.265AI/H.265+.



| Parameter | Details |
|---------------------------|--|
| Model | SS-N8016RV-H2-M5 |
| Make | SECURUS |
| User Interface | Graphic User Interface (GUI) |
| Operating System | Embedded Linux |
| Operation Mode | Preview, Record, Playback, Backup, Network |
| Password Security | Multi-level User Management |
| ONVIF | Support |
| Video Input | 16ch 5M/16ch1080P |
| HDMI Output | 1 x Supports (Max : 4K) |
| VGA Output | Supports (Max : 1080P) |
| CVBS main output | N.A. |
| Audio output | 1 Ch, RCA connector |
| Display | 1/4/6/8/9/10/13/16 optional |
| Video standard | PAL/NTSC |
| Video compression | H.265AI/H.265+/H.265/H.264+/H.264 |
| Intelligent Functions | Face Detection, Vehicle Detection, Human Detection, Active Deterrence, Line Crossing, Trip Wire, People Counting |
| Video encoding resolution | 12MP; 8MP; 5MP; 4MP; 3MP; 1080P |
| Synchronous Playback | 8 Channel |

| Parameter | Details |
|----------------------|---|
| Video frame rate | PAL: 1-25 FPS NTSC: 1-30FPS |
| Video bit rate | 1536kbps-3072kbps |
| Stream Type | Video & Audio/Video |
| Audio compression | G.711a |
| Recording mode | Always/Schedule/Alarm/ recording/Motion detection recording |
| Video search | Time/Channel/Event |
| Display Zoom | Live Playback & Mobile |
| Audio bit rate | 8-32kbps |
| Dual-stream | Supports |
| Mobile Monitoring | "RMEye Pro" Application for Android And iPhone |
| Recording resolution | 16 CH Realtime Recording |
| HDD Port | 2 SATA |
| HDD Maximum Capacity | 12TB for each Sata connector |
| Voice talk | Support; 1CH BNC line in/1CH RCA Audio out. |
| Record mode | Audio & Video recording simultaneously |
| Remote control | Supports |
| Network protocol | Supports IE, TCP/IP, UDP, RTP, RTSP, NTP, HTTP, DHCP, PPPoE, SMTP, DNS, DDNS, HTTPS, SNMP, IPv4/v6, NFS, iSCSI, ONVIF |
| Security | IP address filtering, User access log, 802.1x authentication, Encryption |

| Parameter | Details |
|-----------------------|--|
| Network Bandwidth | 240Mbps Incoming / 240Mbps Outgoing |
| DDNS Server | www.securusddns.com |
| Network | 1 RJ45 10M/100M/1000M |
| USB Connector | 2 x USB2.0 |
| Firmware update | Support USB update/Network update |
| Alarm input | N.A. |
| Alarm output | N.A. |
| Power supply | NVR: DC 12V 4A |
| Operation Temperature | -10°C-- +55°C |
| Operation Humidity | 10%--90% |
| Chassis | Standard 1.5U |
| Dimension | 256mm (W) × 334mm (L) × 52mm (H) |
| Weight(without HDD) | ≤1.0Kg |
| Certifications | CE, FCC, RoHS, BIS |

RMEye Pro Mobile Application




Android



iPhone

Securus Overview

Securus CCTV is one of the Largest Indian Manufacturer & Supplier of Video Surveillance Products like High Definition Cameras, Standalone Recorders, Network Recorders, POE Switches, Video Management Surveillance Software, CCTV & Networking Cables for Surveillance & Other Surveillance Products & Solutions. Powered by In House R&D Team & State-of-the Art Factory in Electronic Zone Gandhinagar. We Manufacture Products under the **Make in India** Initiative.



Securus AI Technology



Head Office

K.M. ELECTRONIC CABLES PRIVATE LIMITED
"K.M. House", Near C.U. Shah College,
Ahmedabad, Gujarat-380014

Factory

K.M. ELECTRONIC CABLES PRIVATE LIMITED
B-20, GIDC Electronics Estate, Sector 25,
Gandhinagar, Gujarat-382024

Email

sales@securuscctv.com

Securus Helpline

85911 85511

Securus Website

www.securuscctv.com