

SECURUS[®]

Security. Never Compromise!!



RMEye Pro




R-72004642

SECURUS SS-N8016RV-H1-M2


16Ch H.265AI Network Recorder with Face Detection

A Professional 16 Channels H.265AI Hardware Compression Standalone. Supports Mobile Viewing on iPhone and Android Mobiles via **RMEye Pro** Application. You can format HDD and control entire device using the mobile application. It has one of the easiest Playback and Backup modes.

SECURUS AI Network Recorder Range
01-12-2019



**FACE
RECOGNITION**



Parameter	Details
Model	SS-N8016RV-H1-M2
Make	SECURUS
User Interface	Graphic User Interface (GUI)
Operating System	Embedded Linux
Operation Mode	Preview, Record, Playback, Backup, Network
Password Security	Multi-level User Management
Video Input	16Ch 5MP(15FPS); 8ch 5MP; 16ch 1080P
HDMI Output	Supports (Max : 4K)
VGA Output	Supports (Max : 1080P)
CVBS main output	N.A.
Audio output	1 Ch, RCA connector
Display	1/4/6/8/9/10/13/16 optional
Video standard	PAL/NTSC
Video compression	H.265AI/H.265+/H.265/H.264+/H.264
Intelligent Functions	Trip Wire, Face Detection
Video encoding resolution	5MP; 4MP; 3MP; 1080P

Parameter	Details
Video frame rate	PAL: 1-25FPS NTSC: 1-30FPS
Video bit rate	1536kbps-3072kbps
Stream Type	Video & Audio/Video
Audio compression	G.711a
Recording mode	Always/Schedule/Alarm/ recording/Motion detection recording
Video search	Time/Channel/Event
Display Zoom	Live Playback & Mobile
Audio bit rate	8—32kbps
Dual-stream	Supports
Mobile Monitoring	"RMEeye Pro" Application for Android And iPhone
Recording resolution	16 CH Realtime Recording
HDD Port	1 SATA
HDD Maximum Capacity	8TB for each Sata connector
Voice talk	Support, 1CH BNC line in/1CH RCA Audio out.
Record mode	Audio & Video recording simultaneously
Remote control	Supports
Network protocol	Supports IE/PPPoE/DDNS

Parameter	Details
DDNS Server	www.securusddns.com
Network	1 RJ45 10M/100M/1000M
USB Connector	3 USB 2.0
Firmware update	Support USB update/Network update
Alarm input	N.A.
Alarm output	N.A.
Power supply	NVR: DC 12V 2A
Operation Temperature	-10°C-- + 55°C
Operation Humidity	10%--90%
Chassis	Standard 1.0U
Dimension	236mm (W) × 255mm (L) × 44mm (H)
Weight(without HDD)	≤1.0Kg
Certifications	CE, FCC, RoHS, BIS.

RMEye Pro Mobile Application



Android



iPhone